

CLAIMS

sub
B1
5 1. Ophthalmic lens consisting of a substrate made of organic glass, of an abrasion-resistant coating, of a layer of impact-resistant primer and of an inorganic anti-reflective coating, characterized in that the surface of the said substrate is covered with the abrasion-resistant coating and in that the impact-resistant primer layer is inserted between the said abrasion-resistant layer and the anti-reflective coating.

10 2. Lens according to claim 1, wherein the substrate is chosen from:

(I) the glasses obtained by polymerization of diethylene glycol bis(allyl carbonate);

(II) the glasses obtained by polymerization of acrylic monomers derived from bisphenol A;

15 (III) the glasses obtained by polymerization of allyl monomers derived from bisphenol A.

3. Lens according to claim 1, wherein the substrate is chosen from:

20 (A) the glasses obtained from poly(methyl methacrylate);

(B) the glasses obtained from polystyrene resin;

(C) the glasses made of resin based on diallyl phthalate.

4. Lens according to claim 1, wherein the impact-resistant interlayer has an intrinsic Bayer value lower than or equal to 2, at a thickness of 3 μm .

25 5. Lens according to claim 1, wherein the impact-resistant primer is a thermoplastic or heat-curable polymer composition which has a solids content ranging from 5 to 20% by weight relative to the total weight of the primer composition.

30 6. Lens according to claim 1, wherein the thickness of the impact-resistant interlayer in the cured state is between 0.2 and 1 μm .

7. Lens according to claim 1, wherein the composition of the impact-resistant primer consists of a thermoplastic polyurethane resin obtained by reaction of a diisocyanate with a compound comprising a reactive hydrogen at each end.

F020304949250

8. Lens according to claim 1, wherein the composition of the impact-resistant primer consists of a heat-curable polyurethane resin obtained by reaction of a blocked polyisocyanate and of a polyol.

9. Lens according to claim 1, wherein the composition of the impact-resistant primer consists of a copolymer of acrylic and/or methacrylic monomers and of aromatic vinyl compounds.

10. Lens according to claim 1, wherein the composition of the impact-resistant primer consists of a polysiloxane.


11. Lens according to claim 10, wherein the composition of the impact-resistant primer contains, in a solvent medium, one or a number of silane hydrolysate(s) with an epoxy group containing at least one Si-alkyl group and containing no fillers.

12. Lens according to claim 1, wherein the hard abrasion-resistant coating is obtained by curing a composition containing:

a) colloidal silica which has a mean particle diameter of between 1 and 100 μm ;

b) a solvent;

c) a hydrolysate or a mixture of hydrolysates of silane compound(s) of formula:



in which:

R^1 denotes an organic group containing an epoxy group;

R^2 is a hydrocarbon radical which has 1 or 2 carbon atoms;

R^3 is a hydrocarbon group which has from 1 to 4 carbon atoms, and a is 0 or 1 in value.

13. Lens according to claim 1, wherein the thickness of the abrasion-resistant layer, in the cured state, is between 1 and 15 μm .

14. Lens according to claim 12, wherein the composition of the abrasive-resistant coating has a colloidal silica content of between 0 and 40% by weight in the solids content.

113
B2

15. Lens according to claim 1, wherein the anti-reflective coating consists of a mono- or multilayer film based on dielectric materials and deposited by vacuum deposition.

16. Lens according to claim 1, successively including :

5 a) a substrate made of glass obtained by polymerization of diethylene glycol bis(allyl carbonate);

b) a hard abrasion-resistant coating obtained by curing a composition containing, in methanol, colloidal silica and a hydrolysate of γ -glycidyloxypropylmethyldiethoxysilane;

10 c) an impact-resistant interlayer obtained by curing a composition containing, in methanol, a hydrolysate of γ -glycidyloxypropylmethyldiethoxysilane or of γ -glycidyloxypropyl-trimethoxysilane;

d) a multilayer anti-reflective coating.

15 17. Lens according to claim 1, successively including :

a) a substrate made of glass obtained by polymerization of diethylene glycol bis (allyl carbonate);

20 b) an abrasion-resistant coating obtained by curing a composition containing, in methanol, colloidal silica and a hydrolysate of γ -glycidyloxypropylmethyldiethoxysilane;

c) an impact-resistant interlayer obtained by (35) curing a composition containing 4,4'-dicyclohexylmethane diisocyanate and polyethylene glycol;

d) a multilayer anti-reflective coating.

25 18. Process for the manufacture of an ophthalmic lens as defined in claim 1, comprising :

- applying the abrasion-resistant coating onto the surface of the organic glass substrate,
- depositing the layer of impact-resistant primer is deposited onto the abrasion-resistant layer ; and
- 30 - depositing the anti-reflective coating is onto the impact-resistant primer.

19. Process according to claim 18, wherein the abrasion-resistant layer and the layer of impact-resistant primer are deposited by

13
 14
 15
 16
 17
 18
 19
 20
 21
 22
 23
 24
 25
 26
 27
 28
 29
 30
 31
 32
 33
 34
 35
 36
 37
 38
 39
 40
 41
 42
 43
 44
 45
 46
 47
 48
 49
 50

20. Process according to claim 18, wherein the abrasion-resistant and impact-resistant primer layers are pretreated using a surface activation treatment by a chemical or physical route.

21. Process according to claim 20, wherein the surface activation treatment is an alkaline chemical etching, an oxygen plasma treatment or an ion bombardment in a vacuum vessel.

AD B47

[illegible]